

Autoclave - Horizontal

Horizontal Cylindrical Pressure Autoclave

This type sterilizer is applicable for medical liquid, instrument and dressing fabric in medical institution and pharmaceutical factory.

Application:

It is applicable for the sterilization of unpacked solid instrument in department of Stomatology, Ophthalmology, Operation room and CSSD.

Features:

- Drying function.
- Interlock function.
- Automatic sterilization process.
- 304 stainless steel material chamber.
- Safety valve for over pressure protection.
- Automatically fill water in case of low water level.
- Over-temperature, over-pressure protection device.
- Water level sensor. The power will be cut-off.
- Double door optional



Models:

Model	LMA-H150	LMA-H200	LMA-H300	LMA-H400	LMA-H500
Capacity	150L	200L	280L	400L	500L
Chamber Size(mm)	φ440*1000	φ515*1000	φ600*1000	φ700*1100	φ700*1300
Working Pressure	0.23MPa				
Working Temp.	134°C				
Temperature Range	105~134°C				
Sterilization Time	0~60 min				
Drying Time	0~60 min				
Temp. accuracy	≤ ±2°C				
Consumption	9KW		12KW	18KW	
Power Supply	220V/380V, 50/60Hz		380V, 50Hz		
External Size (mm)	1400*600*1300		1400*770*1780	1430*880*1830	1800*900*1820
Packing Size (mm)	1500*900*2050		1680*920*2100	1600*1050*2100	1850*1050*2100
Gross Weight (kg)	320		465	530	580

