

ETO Sterilizer

Sterilize critical moisture or heat sensitive items.

Features:

- Negative pressure working system: to guarantee in the whole operation process of EO gas overflow, even if there is leakage, and outside air into the cavity.
- Automatic safety monitoring functions: real-time monitoring of the sterilization chamber pressure changes.
- Effective ventilation to remove residual: automatic pulsing exhaust ventilation system, aim to minimize the epoxy ethane residues.
- Safety door interlock: during operation, unable to open the door.
- Two temperature choices: 55 °C high temperature, 37 °C low temperature.
- Humidification control system: built-in humidity sensor real-time monitoring.
- Power off memory function.
- Electric lift door.

Unique Design Standalone Working Unit

✗ NO External Input Pressure ✗ NO External Input Vacuum

Eto - Ethylene Oxide Sterilization

Eto Sterilization Low Temperature Sterilization Sterilization Methods



FULLY AUTOMATIC OPERATION



Models of Fully Automatic ETO Sterilizer

| LMESeries | Liter Capacity | Size in CM | Model Available | Eto Gas Cartridges | Size in Feet |
|-------------------|----------------|------------|------------------------------------|--------------------|---------------|
| Eto Series LME100 | 100Ltr | 30x30x122 | Stainless Steel / MS Powder Coated | 100Gm | 1x1x4 |
| Eto Series LME120 | 120Ltr | 30x30x140 | Stainless Steel / MS Powder Coated | 100Gm | 1x1x4.6 |
| Eto Series LME135 | 135Ltr | 30x30x152 | Stainless Steel / MS Powder Coated | 100 GM | 1x1x5 |
| Eto Series LME150 | 150Ltr | 38x38x107 | Stainless Steel / MS Powder Coated | 100 GM | 1.25x1.25x3.5 |
| Eto Series LME245 | 245Ltr | 46x46x122 | Stainless Steel / MS Powder Coated | 170 GM | 1.5x1.5x4 |
| Eto Series LME450 | 450Ltr | 61x61x122 | Stainless Steel / MS Powder Coated | 300 GM | 2x2x4 |

